



Testing of the NASA Hypersonics Project's Combined Cycle Engine Large Scale Inlet Mode Transition Experiment (CCE LIMX)

*J.D. Saunders, T.J. Stueber, S.R. Thomas, and K.L. Suder
Glenn Research Center, Cleveland, Ohio*

*L.J. Weir and B.W. Sanders
Techland Research, Inc., North Olmsted, Ohio*

NASA STI Program . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) program plays a key part in helping NASA maintain this important role.

The NASA STI Program operates under the auspices of the Agency Chief Information Officer. It collects, organizes, provides for archiving, and disseminates NASA's STI. The NASA STI program provides access to the NASA Aeronautics and Space Database and its public interface, the NASA Technical Reports Server, thus providing one of the largest collections of aeronautical and space science STI in the world. Results are published in both non-NASA channels and by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.

- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services also include creating custom thesauri, building customized databases, organizing and publishing research results.

For more information about the NASA STI program, see the following:

- Access the NASA STI program home page at <http://www.sti.nasa.gov>
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA STI Help Desk at 443-757-5803
- Telephone the NASA STI Help Desk at 443-757-5802
- Write to:
NASA Center for AeroSpace Information (CASI)
7115 Standard Drive
Hanover, MD 21076-1320



Testing of the NASA Hypersonics Project's Combined Cycle Engine Large Scale Inlet Mode Transition Experiment (CCE LIMX)

J.D. Saunders, T.J. Stueber, S.R. Thomas, and K.L. Suder
Glenn Research Center, Cleveland, Ohio

L.J. Weir and B.W. Sanders
Techland Research, Inc., North Olmsted, Ohio

Prepared for the
58th Joint Army-Navy-NASA-Air Force (JANNAF) Propulsion Meeting
sponsored by the JANNAF Interagency Propulsion Committee
Arlington, Virginia, April 18–22, 2011

National Aeronautics and
Space Administration

Glenn Research Center
Cleveland, Ohio 44135

Trade names and trademarks are used in this report for identification only. Their usage does not constitute an official endorsement, either expressed or implied, by the National Aeronautics and Space Administration.

This work was sponsored by the Fundamental Aeronautics Program at the NASA Glenn Research Center.

Level of Review: This material has been technically reviewed by technical management.

Available from

NASA Center for Aerospace Information
7115 Standard Drive
Hanover, MD 21076-1320

National Technical Information Service
5301 Shawnee Road
Alexandria, VA 22312

Available electronically at <http://www.sti.nasa.gov>

Testing of the NASA Hypersonics Project's Combined Cycle Engine Large Scale Inlet Mode Transition Experiment (CCE LIMX)

J.D. Saunders, T.J. Stueber, S.R. Thomas, and K.L. Suder
National Aeronautics and Space Administration
Glenn Research Center
Cleveland, Ohio 44135

L.J. Weir and B.W. Sanders
Techland Research, Inc.
North Olmsted, Ohio 44070

Abstract

The NASA Fundamental Aeronautics Hypersonics project is focused on technologies for combined cycle, air-breathing propulsion systems to enable highly reliable reusable launch systems for access to space. Turbine Based Combined Cycle (TBCC) propulsion systems offer specific impulse (I_{sp}) improvements over rocket-based propulsion systems in the subsonic takeoff and return mission segments and offer improved safety. The potential to realize more aircraft-like operations with expanded launch site availability and reduced system maintenance are additional benefits.

Among the most critical TBCC enabling technologies as identified in the National Aeronautics Institute (NAI) study were: 1) mode transition from the low speed propulsion system to the high speed propulsion system, 2) high Mach turbine engine development and 3) innovative turbine based combined cycle integration.

To address these key TBCC challenges, NASA's Hypersonics project (TBCC Discipline) initiated an experimental mode transition task that includes an analytic research endeavor to assess the state-of-the-art of propulsion system performance and design codes. This initiative includes inlet fluid and turbine performance codes and engineering-level algorithms. This effort has been focused on the Combined-Cycle Engine Large Scale Inlet Mode Transition Experiment (CCE LIMX) which is a fully integrated TBCC propulsion system with flow path sizing consistent with previous NASA and DoD proposed Hypersonic experimental flight test plans. This experiment is being tested in the NASA Glenn Research Center 10- by 10-ft Supersonic Wind Tunnel (SWT) Facility. The goal of this activity is to address key hypersonic combined-cycle engine issues: (1) dual integrated inlet operability and performance issues—unstart constraints, distortion constraints, bleed requirements, controls, and operability margins, (2) mode-transition sequence elements caused by the switch between the turbine and the ramjet/scramjet flow paths (imposed variable geometry requirements), (3) turbine engine transients (and associated time scales) during transition. The model will be tested in four test phases to develop a unique TBCC database to validate design and analysis tools and address operability, integration, and interaction issues for this class of advanced propulsion systems. The test article installation and facility build-up/preparation was completed and the inlet performance and operability characterization testing commenced on March 7, 2011. The major upcoming events of this activity include:

- Phase I: Parametric inlet characterization testing completed—2nd QTR 2011
- Phase II: Inlet system identification tests completed—3rd QTR 2011
- Phase III: Controlled mode transition with simulated engines demonstrated—3rd QTR 2012
- Phase IV: Controlled mode transition with turbine engine demonstrated—3rd QTR 2013

In this paper we will discuss the following: 1) research objectives addressing TBCC enabling technologies, 2) features of the CCE hardware design which provide a unique TBCC mode transition data

base, 3) experimental procedures and test plans including a discussion of the facility and instrumentation, and 4) a status of the parametric inlet characterization testing.

Introduction

The “National Aeronautics Research and Development Policy” (Ref. 1) document, issued by the National Science and Technology Council in December 2006, stated that one (among several) of the guiding objectives of the federal aeronautics research and development endeavors shall be stable and long-term foundational research efforts. Nearly concurrently, the National Academies issued a more technically focused aeronautics blueprint, entitled: the “Decadal Survey of Civil Aeronautics—Foundations for the Future” (Ref. 2). Taken together these documents outline the principles of an aeronautics maturation plan. Thus, in response to these overarching inputs (and others), the National Aeronautics and Space Administration (NASA) organized the Fundamental Aeronautics Program (FAP), a program within the NASA Aeronautics Research Mission Directorate (ARMD). The FAP initiated foundational research and technology development tasks to enable the capability of future vehicles that operate across a broad range of Mach numbers, inclusive of the subsonic, supersonic, and hypersonic flight regimes.

The FAP Hypersonics Project concentrates on two hypersonic missions: (1) Air-breathing Access to Space (AAS) and (2) the (Planetary Atmospheric) Entry, Decent, and Landing (EDL). The AAS mission focuses on Two-Stage-To-Orbit (TSTO) systems using “air-breathing” combined-cycle-engine propulsion; whereas, the EDL mission focuses on the challenges associated with delivering large payloads to (and from) Mars. So, the FAP Hypersonic Project investments are aligned to achieve mastery and intellectual stewardship of the core competencies in the hypersonic-flight regime, which ultimately will be required for practical systems with highly integrated aerodynamic/vehicle and propulsion/engine technologies. Within the FAP Hypersonics, the technology management is further divided into disciplines including one targeting Turbine-Based Combine-Cycle (TBCC) propulsion. Additionally, to obtain expertise and support from outside (including industry and academia) the hypersonic uses both NASA Research Announcements (NRA’s) and a jointly sponsored, Air Force Office of Scientific Research and NASA, National Hypersonic Science Center that are focused on propulsion research. Finally, these two disciplines use selected external partnership agreements with both governmental agencies and industrial entities.

The TBCC discipline is comprised of analytic and experimental tasks, and is structured into the following two research topic areas: (1) TBCC Integrated Flowpath Technologies, and (2) TBCC Component Technologies. These tasks will provide experimental data to support design and analysis tool development and validation that will enable advances in TBCC technology.

Benefits of TBCC Propulsion

NASA’s Fundamental Aeronautics Program is investigating turbine-based propulsion systems for access to space. TBCC propulsion provides the potential for aircraft-like, space-launch operations that may significantly reduce launch costs and improve safety due to their following characteristics:

1. Turbine-based propulsion systems exhibit significant specific impulse (I_{sp}) improvements over rocket-based propulsion systems in the subsonic takeoff and return mission segments, see Figure 1.
2. Turbine-based systems can mitigate mission risk by providing operational flexibility for all-weather launch, take-off and landing cross-range, powered landing and abort scenarios.
3. Turbine engines afford dual-use capability, adequately serving low speed accelerator missions as well as long range cruise missions.
4. Performance growth margin for TBCCs can be inherently designed for the system, yielding a robust propulsion package that is able to change with mission requirements.

TBCC propulsion for hypersonic applications requires high Mach turbine engines to accelerate the vehicle to scramjet takeover speeds. Major challenges are to develop a turbine accelerator with near Mach 4 capabilities and develop a scramjet with a low ignition speed ($M < 4$) to enable transition from the

low speed to high speed propulsion system. A long term challenge is to understand and design to minimize propulsion system dry weight which can counterbalance the predicted I_{sp} (wet weight) benefit.

TBCC Enabling Technologies

The most critical TBCC enabling technologies as identified in the National Institute of Aerospace study (Ref. 3) were: 1) mode transition from the low speed propulsion system to the high-speed propulsion system, 2) high-Mach turbine engine development, 3) transonic aero-propulsion performance, 4) low-Mach-number dual-mode scramjet operation, 5) Innovative three dimensional flowpath concepts and 6) Innovative turbine-based combined-cycle integration. A further breakout of these TBCC enabling technology challenges are identified in Figure 2.





Figure 1.—Comparison of specific impulse for turbine-based and rocket-based propulsion systems.

TBCC Propulsion Technology Challenge: *Develop Air-Breathing Propulsion Technology for Two-Stage-to-Orbit Vehicles*



High Mach Turbine Tech Challenges:

- Increase Maximum Mach from 2+ → 4+
- Provide thrust margin over entire range (0<M<4+)
 - Light Weight High Temperature Materials
 - Thermal Management
 - High Temperature Bearings and Seals
 - Highly Loaded Turbomachinery
 - Propulsion/Airframe Integration
 - Cocooning and Relight

Scramjet Tech Challenges:

- Reduce Scramjet Ignition Mach Speed (M5 → M3)
- Provide transition speed margin (3<M<4)
 - Variable Geometry
 - Advanced Combustion Schemes
 - Light Weight High Temperature Materials
 - Thermal Management
 - High Temperature Seals
 - Propulsion/Airframe Integration

TBCC Propulsion Technology Challenges

- ✓ addressed by NASA CCE
- ✓ Performance and Operability over flight range
- ✓ Inlet / Engine / Nozzle Integration
- ✓ Propulsion / Airframe Integration
- ✓ Mode Transition / Stage Separation
- Thermal Management
- Transonic Thrust Margin

Figure 2.—Technologies to enable TBCC propulsion for access to space vehicles.

Integrated Inlet Technology

Military Specification (Mil-spec) inlet performance, as measured by total pressure recovery, can be achieved for an inlet carefully designed for single point operation. However for a TBCC system, the inlet must operate over a wide range of flight conditions and distribute the flow with acceptable distortion and unsteadiness to both the turbine engine as well as the dual mode ram/scramjet engine. Common practice is to use variable geometry and designed bleed configurations to enable a wide range of inlet operability and meet performance requirements including maximizing pressure recovery and minimizing flow spillage. However, this added complexity to achieve high performance and operability results in additional weight, complex vehicle integration, and an increase in drag. Figure 4 illustrates that the inlet pressure recovery can vary by a factor of 4X (assuming Mil-spec can be achieved over the Mach flight range) depending on the inlet complexity. Component performance levels (such as total pressure recovery) are used in system trade studies for each vehicle configuration and mission such as air-breathing access to space (AAS). To this end, NASA is focusing on the development of validated design and analysis tools as well as parametric databases which are required to perform these system trade studies.

Specific questions related to integrated inlet technology addressed by the inlet performance and characteristic (Phase I) testing of the Combined Cycle Engine Large Scale Inlet Mode Transition Experiment (CCE LIMX) include:

- Is Mil-Spec performance achievable over the wide operating range that is required for TBCC space access?
- Can design and analysis tools reliably predict inlet performance and operability?
- What is the trade-off between bleed and inlet performance/operability?
- Can design and analysis tools adequately predict operability limits both with and without bleed?
- Can these tools predict low/high speed inlet interaction effects due to varying inlet backpressures and low/high speed inlet cowl positions?




Figure 4.—Potential Inlet Total Pressure Recovery for TBCC inlets.

Inlet/Engine Interactions

In order to maintain propulsion system performance through mode transition, the inlet/engine as well as the low speed/high speed engine interactions must be controlled to avoid inlet unstarts and engine stalls while maintaining the proper airflow quality and splits as the low speed turbine engine is spooled down and the dual mode ramjet takes over. Specific questions with regard to inlet/engine interaction:

- What impact does engine inlet distortion have on performance and operability?
- Can design and analysis tools predict distortion into engine both with and without bleed?
- Can these tools predict the impact of distortion on engine performance and operability?
- What is the trade-off between bleed and inlet exit profile? Are vortex generators required?

Propulsion Mode Transition

Validated design and analysis tools are necessary to model the TBCC propulsion system characteristics over the wide flight range and during mode transition. This requires addressing specific questions with regard to understanding and demonstrating mode transition:

- What is the process for safe and optimum mode transition?
- Can design and analysis tools properly model components adequately to perform a controlled mode transition?
- Are these predictions of sufficiently high fidelity to guide the testing and avoid inlet unstart and/or engine stall?
- Can these design tools be effectively used to extrapolate the experimental data in order to optimize the propulsion system configuration?

Throughout the CCE LIMX testing, this model will be used as a testbed to assess the state-of-the-art of performance and design codes/tools, inclusive of fluid and turbine performance codes and engineering-level algorithms. During this activity integrated system design and analysis tools, as well as dynamic models, are being developed and validated to support the controls design and demonstration of mode transition of an over-under TBCC propulsion system.

CCE LIMX—Testbed for Mode Transition Testing

The CCE LIMX is a dual integrated inlet flowpath designed for mode transition testing, including controls and integrated inlet and engine testing. The unique features of the CCE LIMX that are being used to develop databases and assess state-of-the-art (SOA) tools are shown in Figure 5.

There are four phases in the test activity that span approximately 3 years: Phase I: inlet performance and operability characterization in which cold pipe and mass flow plugs are used to simulate engine backpressures for both the low-speed and high-speed flow paths. Open loop control mode transition sequences will also be demonstrated. Phase II: unsteady Inlet dynamic system identification experiments using the cold pipe and mass flow plugs installed in both flowpaths. This test phase will provide the data needed to develop the closed loop propulsion system controller. Phase III: demonstrate closed loop mode transition control strategies using the cold pipe and mass flow plugs installed in both flowpaths. Phase IV: demonstrate closed loop controlled mode transition strategies with a candidate turbine engine and single expansion ramp nozzle (SERN) system incorporated into the low-speed flowpath (see Appendix). As currently planned the high-speed flowpath uses the cold pipe and mass flow plugs to simulate the ram/scramjet for all four phases.

10x10 TBCC/CCE Testbed : Inlet Characterization & Mode Transition Test: **Develops**
Operability, Performance and Control Models




Figure 5.—Unique features of the CCE LIMX to develop databases and assess SOA tools.

The CCE LIMX has substantial parametric capability; it has a reconfigurable bleed system, variable-geometry flow paths, and accommodates a nominally 12-in. diameter turbine. There are a total of 13 bleed locations (controlled by 15 cold pipe/mass flow plug assemblies) in the low speed flowpath: five on the ramp, three on each of the sidewalls, and two on the cowl. Cold pipe and mass flow plug assemblies are used on the low speed and high speed flow paths to measure flowrate and to backpressure the inlet. The mass flow plugs and cold pipes integrated with the CCE LIMX model are shown in Figure 6. Additionally, due to the large scale, the inlet model is highly instrumented; therefore, spatially resolved distributions and high fidelity data can be obtained.

The CCE research objectives include:

1. Proof of concept of an over/under split flow inlet for a TBCC propulsion system.
 - a. Develop an integrated performance and operability database
 - b. Demonstrate mode transition at large scale.
2. Validate inlet computational fluid dynamic (CFD) code predictions of performance and operability for the low-speed and high speed flowpaths.
3. Develop realistic distortion characteristics throughout the mode transition Mach number range and assess the impact of this distortion on the turbine engine performance and operability.
4. Use this hardware as a testbed for future mode transition controls research and integrated inlet/engine propulsion system studies.

The 10- by 10-ft SWT can operate over a Mach number range of 2 to 3.5 (Ref. 6). The CCE LIMX is mounted to the facility strut and the angle of attack can be varied between -15° and 5° by rotating the strut about its pivot pin which has a 3 in diameter. By operating the facility at Mach 3.5 and positioning the CCE LIMX model at an angle of about -7° , as shown in Figure 7, a Mach 4 test condition is provided (which is the design condition); some off-design testing at other Mach numbers will also be conducted.





Figure 6.—CCE LIMX mass-flow plug and cold pipe locations.




Figure 7.—CCE LIMX Model orientation in the 10- by 10-ft SWT.

The CCE LIMX development was led by NASA with many partners playing an integral role in the design and development. Techland Research, Inc. was the primary contractor for the inlet aerodynamic flowpath design (Ref. 5). Alliant Techsystems, Inc. (ATK) had the primary responsibility for the mechanical design and integration of the inlet hardware and also provided a candidate scramjet design which was carried through detailed design. Arctic Slope Regional Corporation (ASRC) also helped with mechanical design and were responsible for much of the design and fabrication of the facility hardware including the strong back. Metalex, Inc. fabricated the majority of the inlet test rig hardware. Williams International is providing the (high Mach) turbine engine via an interagency agreement between NASA and the Air Force Research Lab (AFRL) to develop high speed turbine engines. The integrated turbine engine nozzle was designed and fabricated by Spiritech, Inc. Boeing, Inc. contributed with CFD simulations which helped with test preparations. The collage shown in Figure 8 illustrates the contributions of the CCE testbed hardware team.




Figure 8.—CCE Testbed and Mode Transition Team.

Facility Preparation and CCE LIMX Model Installation

CCE LIMX preparations have been underway for over 3 years. Installation of the test article and all facility preparations were completed, and Phase I testing commenced March 7, 2011.

Due to the large scale of the test article, its complexity, and the extent of instrumentation, the process of carefully installing this test article took place through most of calendar year 2010. The test team took the time and care during installation to make certain the flowpath was configured as designed. The inlet model was delivered to the 10- by 10-ft SWT facility in January 2010 and mounted into the tunnel by February 2010 (Fig. 9(a)). Upon receipt and installation of the hardware, a need to re-work many of the seals and make some modifications to the hardware was determined. This subsequently required substantial disassembly, rework, and reassembly. During re-work, the model was disassembled, leak paths were sealed, and the instrumentation routing was completed. Between March and September 2010 the model was reassembled, which included the installation of all cold pipe and mass flow plug assemblies as shown in Figure 9(b). The forebody pre-compression plate, which is the trapezoidal shaped surface shown in Figure 9(c), was then installed onto the facility strut and aligned with the inlet model. Final instrumentation end-to-end checks, calibration of all moving systems (17 mass flow plugs, two cowls, ramp, and strut angle) were conducted. The overall integrated systems testing, pre-test checkouts, and all required safety and test readiness reviews were completed October 2010 through February 2011; testing commenced on March 7, 2011.




Figure 9.—(a) Model as delivered and subsequently mounted in the facility (Jan. to Feb. 2010). (b) Model partly disassembled to work seals and hardware interfaces, instrumentation routing, checked out, and inlet model re-assembled (Mar. to Sep. 2010). (c) CCE LIMX installed in the 10- by 10-ft SWT ready for test.

CCE LIMX Testing

Four test phases to address the technical challenges and questions discussed previously are planned over the next 3 years. Phase I commenced on March 7, 2011, and is expected to conclude by the end of May 2011. Previous studies were used to mitigate risk and guide preparations for these experiments (Ref. 7). These efforts included CFD analysis (Ref. 8) as well as smaller scale screening tests (Ref. 9) in the NASA Glenn 1- by 1-ft supersonic wind tunnel. The small scale test results and the CFD analysis were used to set initial bleed schedules, assess sensitivity to performance and operability with variable geometry (both cowl, and low speed ramp), identify necessary control models (Ref. 10), and to help develop the test plan. The CCE LIMX has substantially more parametric capability than the small scale test model and is more highly instrumented to provide improved fidelity of results. By using the small scale test and computational results, an initial test plan for the Phase I experiment was developed as shown in Table I.

TABLE I.—TEST MATRIX FOR THE CCE LIMX INLET CHARACTERIZATION (PHASE I)

Test series	Bleed pattern	Vortex generator configuration	Simulated Mach numbers	Notes	Planned data points
1	A7	Basic	4	Facility and model checkout run	7
2	A7	Basic	4	Configuration a7, testing at lower pressure	165
3	A7	Basic	4	Configuration a7, start of standard testing	204
4	A8	Basic	4	Alternate bleed configuration, a8	204
5	A9	Basic	4	Alternate bleed configuration, a9	204
6	Selected	Basic	4	Alternate cowl lip al	204
7	Selected	Vgl	4	Alternate vortex generator pattern	204
8	Selected	Selected	4	Performance and mode transition	661
9	Selected, reduced bleed	Selected	4	Reduced bleed	204
10	Selected	Selected	3	Lower (off design) mach number tests	661
11	Selected, reduced bleed	Selected	3	Lower (off design) mach number tests	204
12	Selected	Selected	3.5	Lower (off design) mach number tests	223
13	Selected	Selected	2.5	Lower (off design) mach number tests	223
14	Selected	Selected	2	Lower (off design) mach number tests	223

Due to high electrical power usage, testing of the 10- by 10-ft SWT occurs on third shift. At the time of the writing of this report 10 nights of testing have been conducted. The 10- by 10-ft SWT is a continuous flow facility and substantial data can be obtained in a test period. For any supersonic tunnel, model size is a concern due to blockage, or the ability to ‘pass the [tunnel normal] shock’ and start the tunnel. Initial testing has first shown that the supersonic tunnel was able to start and operate nominally with this large model installed (Refs. 6 and 11). During the second test period a hard facility shutdown (or tunnel unstart) was observed, which produced a high pressure load over the model. Because the hardware was structurally designed to handle this event, the tunnel unstart did not result in any facility or model damage.

With this experience complete, testing is progressing with substantial research testing has been achieved to date. Several hundred data points have been taken and are being analyzed; the first configurations for the low speed and the high speed flowpaths have been initially characterized and the performance assessed. Access to this data can be obtained through the authors and will be reported out in detail in the near future. The results are being compared to pre-test computational solutions and to the small scale inlet mode transition experiment (IMX) results previously obtained in 1- by 1-ft SWT. Phase I and II testing are planned to be completed during 2011 (expected to conclude August 2011); Phase III in 2012, and Phase IV in 2013.

Summary and Concluding Remarks

One of the missions of the NASA Aeronautics Research Directorate (ARMD) Fundamental Aeronautics Program (FAP) Hypersonics project is to develop air-breathing propulsion technology for air-breathing access to space (AAS). The focus of this effort is in developing a two stage to orbit (TSTO) turbine based combined cycle (TBCC) propulsion system.

There are many technical challenges involved with the development of a TBCC propulsion system and these were discussed in this paper. The TBCC Discipline of the Hypersonics project is pursuing the Combined Cycle Engine Large Scale Inlet Mode Transition Experiment (CCE LIMX) to work towards answering these questions. This very complex experimental activity will take place over the next three years and will be accomplished through 4 distinct phases of testing. Phases I through III use the initial test article configuration, which is presently being tested in the NASA Glenn 10- by 10-ft SWT, and includes mass flow plug and cold pipe assemblies in both the low speed and high speed flowpaths. For Phase IV, a high Mach capable turbine engine and single expansion ramp nozzle (SERN) will be incorporated into the low-speed flowpath. This engine and nozzle have also been developed as a part of the TBCC discipline activity.

Over the past 3 years the CCE LIMX hardware has been developed, designed, fabricated, installed, checked out, and is now being tested in the 10- by 10-ft SWT. Testing commenced on March 7, 2011, and to date 10 nights of testing have been conducted. Initial testing has shown that the supersonic tunnel was able to easily start and operate nominally with this large model installed, and a hard facility shutdown was experienced without any resultant facility or model damage. Already several hundred data points have been obtained, since this is a continuous flow facility, and these are being analyzed. Access to the data can be obtained through the authors and will be reported out in detail in the near future.

Overall this test activity is providing a highly accurate, refined database on this TBCC design and will serve to demonstrate the controlled mode transition which is required by an advanced air-breathing propulsion system to enable hypersonic flight. Beyond the four phases of this current study the CCE LIMX test hardware/TBCC testbed will be continue to remain available to address future national needs in combined cycle propulsion.

References

1. Marburger, John H., et al., "National Aeronautics Research and Development Policy," National Research and Technology Council, December 2006.
2. "Decadal Survey of Civil Aeronautics—Foundations for the Future," National Academies, June 2006.
3. NIA Report, Boeing Contractor Report, Contract No. 2900-HY04, February 18, 2005.
4. Bilardo V.J., Curran F.M., Hunt J.L., Lovell N.T., Wilhite A.W., McKinney L.E., "The Benefits of Hypersonic Airbreathing Launch Systems for Access to Space," AIAA 2003-5265, 39th AIAA/ASME/SAE/ASEE Joint Propulsion Conference, Huntsville, AL, 20-23 July 2003
5. Sanders, B. W.; and Weir, L. J.: "Aerodynamic Design of a Dual-Flow Mach 7 Hypersonic Inlet System for a Turbine-Based Combined-Cycle Hypersonic Propulsion System," NASA/CR—2008-215214, June 2008.
6. Soeder, R.H, Roeder, J.W., Linne, A.A., and Panek, J.W., "User Manual for NASA Glenn 10-by10-Foot Supersonic Wind Tunnel," NASA/TM—2004-212697, May 2004.
7. Saunders J.D., Slater J.W., Dippold V., Weir, L.J., Sanders B.W., "Inlet Research Status for a Large-Scale Turbine-Based Combined Cycle Engine Testbed", JANNAF, La Jolla, CA, (Dec. 7-11, 2009).
8. J. W. Slater and J. D. Saunders: CFD Simulation of Hypersonic TBCC Inlet Mode Transition, AIAA-2009-7349, 16th AIAA/DLR/DGLR International Space Planes and Hypersonic Systems and Technologies Conference, Oct.2009.
9. J. D. Saunders; J. W. Slater; V. Dippold; J. Lee; B. W. Sanders and L. J. Weir: "Inlet Mode Transition Screening Test for a Turbine-Based Combined-Cycle Propulsion System," JANNAF, Boston, MA (May 13, 2008).

10. Stueber, T.J.; Vrnak, D.R.; Le, D.K.; and Ouzts, P.J.: "Control Activity in Support of NASA TBCC Research," JANNAF, La Jolla, CA (Dec. 7-11, 2009).
11. Liepmann, H.W.; and Roshko, A.: Elements of Gasdynamics, pp. 130-137, John Wiley & Sons, Inc. 1957.

Appendix—Mach 3 Capable Turbine Development

The CCE LIMX Phase IV task includes removing the cold pipe and mass flow plug assembly from the low-speed flowpath and installing a Mach 3 capable turbine engine in its place. In preparation for this test a Williams International WJ38 Turbine Engine has been modified as required for Mach 3 operation. The engine is currently available and has undergone sea level static (SLS) checkout tests. A final series of checkout/acceptance testing is planned with an afterburner and integrated nozzle installed. Figure 10 shows a photo of the WI turbine and the integrated nozzle assembly; this hardware will be delivered to NASA at the conclusion of the checkout testing (expected April 2011).




Figure 10.—Williams International High Mach WJ38 turbine engine and integrated nozzle assembly.

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</p>					
1. REPORT DATE (DD-MM-YYYY) 01-01-2012		2. REPORT TYPE Technical Memorandum		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE Testing of the NASA Hypersonics Project's Combined Cycle Engine Large Scale Inlet Mode Transition Experiment (CCE LIMX)				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Saunders, J., D.; Stueber, T., J.; Thomas, S., R.; Suder, K., L.; Weir, L., J.; Sanders, B., W.				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER WBS 599489.02.07.03.07.11.01	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration John H. Glenn Research Center at Lewis Field Cleveland, Ohio 44135-3191				8. PERFORMING ORGANIZATION REPORT NUMBER E-17898	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Washington, DC 20546-0001				10. SPONSORING/MONITOR'S ACRONYM(S) NASA	
				11. SPONSORING/MONITORING REPORT NUMBER NASA/TM-2012-217217	
12. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified-Unlimited Subject Category: 07 Available electronically at http://www.sti.nasa.gov This publication is available from the NASA Center for AeroSpace Information, 443-757-5802					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT Status on an effort to develop Turbine Based Combined Cycle (TBCC) propulsion is described. This propulsion technology can enable reliable and reusable space launch systems. TBCC propulsion offers improved performance and safety over rocket propulsion. The potential to realize aircraft-like operations and reduced maintenance are additional benefits. Among most the critical TBCC enabling technologies are: 1) mode transition from turbine to scramjet propulsion, 2) high Mach turbine engines and 3) TBCC integration. To address these TBCC challenges, the effort is centered on a propulsion mode transition experiment and includes analytical research. The test program, the Combined-Cycle Engine Large Scale Inlet Mode Transition Experiment (CCE LIMX), was conceived to integrate TBCC propulsion with proposed hypersonic vehicles. The goals address: (1) dual inlet operability and performance, (2) mode-transition sequences enabling a switch between turbine and scramjet flow paths, and (3) turbine engine transients during transition. Four test phases are planned from which a database can be used to both validate design and analysis codes and characterize operability and integration issues for TBCC propulsion. In this paper we discuss the research objectives, features of the CCE hardware and test plans, and status of the parametric inlet characterization testing which began in 2011. This effort is sponsored by the NASA Fundamental Aeronautics Hypersonics project.					
15. SUBJECT TERMS Turbine engines; Ramjet engines; Scramjet engines; Propulsion					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			STI Help Desk (email: help@sti.nasa.gov)
U	U	U	UU	22	19b. TELEPHONE NUMBER (include area code) 443-757-5802

